

CASSIDA Product Information



LUBRITECH
Special Application Lubricants

CASSIDA FLUID GLE Series

Enhanced performance synthetic gear lubricants for food and beverage processing equipment



Gears – enclosed



Roller Bearings



Can Seamers and Sterilisers



NSF registered

Description

CASSIDA FLUID GLE 150 and 220 are fully synthetic, high performance, antiwear gear lubricants, specifically designed for use in the food and beverage canning industry.

They are based on a careful blend of synthetic fluids and selected additives chosen for their ability to meet the stringent requirements of the food and beverage industry.

Certified by NSF for ISO 21469 and registered by NSF (Class H1) for use where there is potential for incidental food contact. Produced according to LUBRITECH Quality Standards, in facilities where HACCP audit and Good Manufacturing Practice have been implemented and form part of the quality and hygiene management systems ISO 9001 and ISO 21469.

Certifications and Specifications

- NSF H1
- NSF ISO 21469
- Kosher
- Halal
- DIN 51517 CLP

Performance Features

- The fully synthetic base fluid has been selected for its ability to provide superior lubrication under variety of applications
- Specially formulated to provide excellent lubrication even when operating in locations where it is subject to contamination with water, juice and food, which is held in suspension, thus protecting metal surfaces from wear and corrosion

CASSIDA Product Information



LUBRITECH
Special Application Lubricants

- Excellent separation properties, from water, in oil re-circulation and filtration systems
- Neutral odor and taste
- Good anti-oxidant properties. Resists the formation of deposits and sludge even at elevated temperatures resulting in long oil and equipment life

Applications

- Lubrication of rotary can seaming machines equipped with either enclosed (re-circulation) or total loss systems
- Circulating and bearing oil systems where contamination with water or food juice can occur, such as citrus juice extraction machines

Seal and paint compatibility

Compatible with the elastomers, gaskets, seals and paints normally used in food machinery lubrication systems.

Handling and storage

All food grade lubricants should be stored separately from other lubricants, chemical substances and foodstuffs and out of direct sunlight or other heat sources. Store between 32°F and 100°F. Provided that the product has been stored under these conditions we recommend to use the product within 5 years from the date of manufacture. Upon opening a pack, the product must be used within 2 years (or within 5 years of date of manufacture, whichever is sooner).

CASSIDA Product Information



LUBRITECH
Special Application Lubricants

Typical characteristics

Property	CASSIDA FLUID GLE 150	CASSIDA FLUID GLE 220	Unit	Test Method
NSF Reg. No.	147341	147342		
Colour	Colourless to Yellow	Colourless to Yellow		
Density at +15 °C	849	852	Kg/m ³	ISO 12185
Flashpoint	258 (496)	270 (518)	°C (°F)	ISO 2592
Pourpoint	-54 (-65)	-48 (-54)	°C (°F)	ISO 3016
Kin. Visc. (base oil) at +40 °C	150	220	mm ² /s	ISO 3104
Kin. Visc. (base oil) at +100 °C	19.0	25.0	mm ² /s	ISO 3104
Viscosity index	140	143		ISO 2909
FZG-Test A/8.3/90 Failure Load Stage	>12	>12		ISO 14635-1

As far as we know these information reflect the current state of knowledge and our research. They cannot, however, be taken as an assurance about the properties nor as a guarantee of the suitability of the product for the individual case in point. Before using our products the purchaser must, therefore, check the suitability and be satisfied that the output will be satisfactory. Our products are continually being up-dated. We reserve the right, therefore, to alter the information of this product information at any time and without prior announcement. We are specialized in developing products for extreme tribological problems in cooperation with end users. FUCHS LUBRITECH provides service and individual advice. Please contact us! E-Mail: Lubritech-US@fuchs.com